

number of cores xNominal cross Section	overall diameter	weight	Maxinum conductor Resistance	Minimun breaking Load	current Rating
No.xmm ²	mm	kg/km	Ω/Km	KN	A
1x16+1x25 RM	15.3	160	1910	2,5	72
3x16+1x25 RM	19	290	1200	4,0	107
3x25+1x25 RM	23.2	400	0,868	5,5	132
3x35+1x25 RM	25.6	500	0,641	8,0	165
3x50+1x35 RM	30	680	0,443	10,7	205
3x70+1x50 RM	34.9	920	0,320	13,7	240
3x95+1x70 RM	40.6	1270	0,253	18,6	290
3x120+1x70 RM	44.1	1510	0,206	23,2	334
3x150+1x95 RM	49.2	1870	0,164	28,7	389
3x185+1x120 RM	54.9	2340	0,125	37,2	467
3x25+1x25+1x16 RM	23.2	470	1910	2,5	72
3x35+1x25+1x16 RM	25.6	560	1200	4,0	107
3x50+1x35+1x16 RM	30	740	0,868	5,5	132
3x70+1x50+1x16 RM	34.9	980	0,641	8,0	165
3x95+1x70+1x16 RM	40.6	1330	0,443	10,7	205
3x120+1x70+1x16 RM	44.1	1580	0,320	13,7	240
3x150+1x95+1x16 RM	49.2	1940	0,206	23,2	334
3x185+1x120+1x16 RM	54.9	2410	1910	2,5	72