

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²		NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
	Phase Conducto	Earth Conductor				
1	95	-	1.1	1.5	16.5	390
1	120	-	1.2	1.8	17.7	465
1	150	-	1.4	1.8	20.1	580
1	185	-	1.6	1.8	22.1	715
1	240	-	1.7	1.8	25.0	905
1	300	-	1.8	1.8	27.5	1120
1	400	-	2	1.9	31.4	1440
1	500	-	2.2	2	34.6	1770
1	630	-	2.4	-	37.0	2180
3	70	35	1.1	1.9	33.0	1450
3	95	50	1.1	2.1	37.3	1910
3	120	70	1.2	2.2	41.5	2410
3	150	70	1.4	2.3	49.0	3535
3	185	95	1.6	2.5	51.0	3810
3	240	120	1.7	2.7	58.0	4880
3	300	150	1.8	2.8	64.2	5610
4	16	16	0.9	1.8	22.4	675
4	25	16	0.9	1.8	26.0	910
4	35	16	0.9	1.8	28.7	1120
4	50	25	1	1.8	33.0	1475
4	70	35	1.1	1.9	38.0	1985
4	95	50	1.1	2.1	43.0	2580
4	120	70	1.2	2.2	47.2	3175
4	150	70	1.4	2.3	54.2	4035
4	185	95	1.6	2.5	59.4	4945
4	240	120	1.7	2.7	68.1	6425
4	300	150	1.8	2.8	75.1	7910