

Rated Voltage	No.OF CORES	CORSS SECTIONAL AREA(MM2)	CONDUCTOR	CORE DIAMETER(MM)	CONDUCTOR SCREEN THICKNESS(MM)	INSULATION THICKNESS(MM)	NON-METAL SCREEN SIZE(MM)	METAL SCREEN SIZE(MM)	BELT(MM)	JACKET THICKNESS(MM)	OVERALL DIAMATER (MM)	WEIGHT(KG/KM)	DC RESISTANCE (OHM/KM)
3.6/6KV	3	25	7/2.18	6	0.8	2.5	0.7	30×0.10	60×0.20	2.1	35.6	1674.8	0.727
	3	35	7/2.58	7	0.8	2.5	0.7	30×0.10	60×0.20	2.1	37.8	2030.8	0.524
	3	50	10/2.58	8.4	0.8	2.5	0.7	30×0.10	60×0.20	2.2	41	2549.10	0.387
	3	70	19/2.18	10	0.8	2.5	0.7	30×0.10	60×0.20	2.4	44.8	3260.6	0.268
	3	95	19/2.58	11.6	0.8	2.5	0.7	40×0.10	60×0.20	2.5	48.5	4141	0.193
	3	120	24/2.58	13	0.8	2.5	0.7	40×0.10	60×0.20	2.6	51.7	4968.7	0.153
	3	150	30/2.58	14.6	0.8	2.5	0.7	40×0.10	60×0.20	2.7	55.3	5955.5	0.124
	3	185	37/2.58	16.2	0.8	2.5	0.7	40×0.10	60×0.20	2.8	59	7081.9	0.0991
	3	240	48/2.58	18.5	0.8	2.6	0.7	40×0.10	60×0.20	3	64.8	8892.8	0.0754
	3	300	60/2.58	20.6	0.8	2.8	0.7	40×0.10	60×0.20	3.2	70.5	10875.2	0.0601
3	400	61/2.94	23.8	0.8	3	0.7	40×0.10	60×0.20	3.4	78.7	13928.6	0.047	
6/6KV	3	25	7/2.18	6	0.8	3.4	0.7	30×0.10	60×0.20	2.2	39.7	1913.5	0.727
	3	35	7/2.58	7	0.8	3.4	0.7	30×0.10	60×0.20	2.3	42	2299.2	0.524
	3	50	10/2.58	8.4	0.8	3.4	0.7	40×0.10	60×0.20	2.4	45.2	2837.2	0.387
	3	70	19/2.18	10	0.8	3.4	0.7	40×0.10	60×0.20	2.5	48.9	3551.8	0.268
	3	95	19/2.58	11.6	0.8	3.4	0.7	40×0.10	60×0.20	2.6	52.5	4451.6	0.19
	3	120	24/2.58	13	0.8	3.4	0.7	40×0.10	60×0.20	2.7	55.8	5298.8	0.153
	3	150	30/2.58	14.6	0.8	3.4	0.7	40×0.10	60×0.20	2.8	59.4	6306.2	0.124
	3	185	37/2.58	16.2	0.8	3.4	0.7	40×0.10	60×0.20	2.9	63.1	7453.3	0.0991
	3	240	48/2.58	18.5	0.8	3.4	0.7	40×0.10	60×0.20	3.1	68.4	9253.6	0.0754
	3	300	60/2.58	20.6	0.8	3.4	0.7	40×0.10	60×0.20	3.3	73.3	11175.4	0.0601
3	400	61/2.94	23.8	0.8	3.4	0.7	40×0.10	60×0.20	3.5	80.6	14160.5	0.047	
6/10KV	3	25	7/2.18	6	0.8	3.4	0.7	30×0.10	60×0.20	2.2	39.7	1913.5	0.727
	3	35	7/2.58	7	0.8	3.4	0.7	30×0.10	60×0.20	2.3	42	2299.2	0.524
	3	50	10/2.58	8.4	0.8	3.4	0.7	30×0.10	60×0.20	2.4	45.2	2837.2	0.387
	3	70	19/2.18	10	0.8	3.4	0.7	40×0.10	60×0.20	2.5	48.9	3551.8	0.27
	3	95	19/2.58	11.6	0.8	3.4	0.7	40×0.10	60×0.20	2.6	52.5	4451.6	0.193
	3	120	24/2.58	13	0.8	3.4	0.7	40×0.10	60×0.20	2.7	55.8	5298.8	0.153
	3	150	30/2.58	14.6	0.8	3.4	0.7	40×0.10	60×0.20	2.8	59.4	6306.2	0.124
	3	185	37/2.58	16.2	0.8	3.4	0.7	40×0.10	60×0.20	2.9	63.1	7453.3	0.0991
	3	240	48/2.58	18.5	0.8	3.4	0.7	40×0.10	60×0.20	3.1	68.4	9253.6	0.0754
	3	300	60/2.58	20.6	0.8	3.4	0.7	40×0.10	60×0.20	3.3	73.3	11175.4	0.0601
3	400	61/2.94	23.8	0.8	3.4	0.7	40×0.10	60×0.20	3.5	80.6	14160.5	0.047	
8.7/10KV	3	25	7/2.18	6	0.8	4.5	0.7	30×0.10	60×0.20	2.4	44.8	2251.6	0.727
	3	35	7/2.58	7	0.8	4.5	0.7	40×0.10	60×0.20	2.5	47.2	2655.9	0.524
	3	50	10/2.58	8.4	0.8	4.5	0.7	40×0.10	60×0.20	2.6	50.4	3217.3	0.387
	3	70	19/2.18	10	0.8	4.5	0.7	40×0.10	60×0.20	2.7	54	3957.2	0.27
	3	95	19/2.58	11.6	0.8	4.5	0.7	40×0.10	60×0.20	2.8	57.7	4884.7	0.193
	3	120	24/2.58	13	0.8	4.5	0.7	40×0.10	60×0.20	2.9	60.9	5754.2	0.153
	3	150	30/2.58	14.6	0.8	4.5	0.7	40×0.10	60×0.20	3	64.5	6788	0.124
	3	185	37/2.58	16.2	0.8	4.5	0.7	40×0.10	60×0.20	3.1	68.2	7961.6	0.0991
	3	240	48/2.58	18.5	0.8	4.5	0.7	40×0.10	60×0.20	3.3	73.5	9801.3	0.0754
	3	300	60/2.58	20.6	0.8	4.5	0.7	40×0.10	60×0.20	3.4	78.3	11725.3	0.0601
3	400	61/2.94	23.8	0.8	4.5	0.7	40×0.10	60×0.20	3.7	85.8	14799.2	0.047	

Rated Voltage	No.OF CORES	CORSS SECTIONAL AREA(MM2)	CONDUCTOR	CORE DIAMETER(MM)	CONDUCTOR SCREEN THICKNESS(MM)	INSULATION THICKNESS(MM)	NON-METAL SCREEN SIZE(MM)	METAL SCREEN SIZE(MM)	BELT(MM)	JACKET THICKNESS(MM)	OVERALL DIAMATER (MM)	WEIGHT(KG/KM)	DC RESISTANCE (OHM/KM)
8.7/15KV	3	25	7/2.18	6	0.8	4.5	0.7	30×0.10	60×0.20	2.4	44.8	2251.6	0.727
	3	35	7/2.58	7	0.8	4.5	0.7	40×0.10	60×0.20	2.5	47.2	2655.9	0.524
	3	50	10/2.58	8.4	0.8	4.5	0.7	40×0.10	60×0.20	2.6	50.4	3217.3	0.387
	3	70	19/2.18	10	0.8	4.5	0.7	40×0.10	60×0.20	2.7	54	3957.2	0.27
	3	95	19/2.58	11.6	0.8	4.5	0.7	40×0.10	60×0.20	2.8	57.7	4884.7	0.193
	3	120	24/2.58	13	0.8	4.5	0.7	40×0.10	60×0.20	2.9	60.9	5754.2	0.153
	3	150	30/2.58	14.6	0.8	4.5	0.7	40×0.10	60×0.20	3	64.5	6788	0.124
	3	185	37/2.58	16.2	0.8	4.5	0.7	40×0.10	60×0.20	3.1	68.2	7961.6	0.0991
	3	240	48/2.58	18.5	0.8	4.5	0.7	40×0.10	60×0.20	3.3	73.5	9801.3	0.0754
	3	300	60/2.58	20.6	0.8	4.5	0.7	40×0.10	60×0.20	3.4	78.3	11725.3	0.0601
12/20KV	3	400	61/2.94	23.8	0.8	4.5	0.7	40×0.10	60×0.20	3.7	85.8	14799.2	0.047
	3	35	7/2.58	7	0.8	5.5	0.7	40×0.10	60×0.20	2.6	51.7	2992.9	0.524
	3	50	10/2.58	8.4	0.8	5.5	0.7	40×0.10	60×0.20	2.7	54.9	3574.5	0.387
	3	70	19/2.18	10	0.8	5.5	0.7	40×0.10	60×0.20	2.8	58.5	4337.1	0.268
	3	95	19/2.58	11.6	0.8	5.5	0.7	40×0.10	60×0.20	2.9	62.2	5287.4	0.19
	3	120	24/2.58	13	0.8	5.5	0.7	40×0.10	60×0.20	3	65.4	6177	0.15
	3	150	30/2.58	14.6	0.8	5.5	0.7	40×0.10	60×0.20	3.1	69.1	7235	0.12
	3	185	37/2.58	16.2	0.8	5.5	0.7	40×0.10	60×0.20	3.3	72.9	8463	0.10
	3	240	48/2.58	18.5	0.8	5.5	0.7	40×0.10	60×0.20	3.4	78.1	10304.9	0.08
	3	300	60/2.58	20.6	0.8	5.5	0.7	40×0.10	60×0.20	3.6	83	12294.3	0.0601
18/30KV	3	400	61/2.94	23.8	0.8	5.5	0.7	40×0.10	60×0.20	3.8	90.3	15377.9	0.047
	3	50	10/2.58	8.4	0.8	8	0.7	40×0.10	60×0.20	3.1	66.5	4635.5	0.387
	3	70	19/2.18	10	0.8	8	0.7	40×0.10	60×0.20	3.2	70.1	5457.3	0.268
	3	95	19/2.58	11.6	0.8	8	0.7	40×0.10	60×0.20	3.3	73.8	6467.1	0.193
	3	120	24/2.58	13	0.8	8	0.7	40×0.10	60×0.20	3.4	77	7409.2	0.153
	3	150	30/2.58	14.6	0.8	8	0.7	40×0.10	60×0.20	3.5	80.6	8525	0.124
	3	185	37/2.58	16.2	0.8	8	0.7	40×0.10	60×0.20	3.6	84.3	9780.7	0.0991
	3	240	48/2.58	18.5	0.8	8	0.7	40×0.10	60×0.20	3.8	89.6	11742.3	0.0754
	3	300	60/2.58	20.6	0.8	8	0.7	40×0.10	60×0.20	3.9	94.3	13770.1	0.0601
21/35KV	3	400	61/2.94	23.8	0.8	8	0.7	40×0.10	60×0.20	4.2	101.8	17015.2	0.047
	3	50	10/2.58	8.4	0.8	9.3	0.7	40×0.10	60×0.20	3.3	72.5	5259.5	0.387
	3	70	19/2.18	10	0.8	9.3	0.7	40×0.10	60×0.20	3.4	76.1	6112	0.268
	3	95	19/2.58	11.6	0.8	9.3	0.7	40×0.10	60×0.20	3.5	79.8	7152.4	0.193
	3	120	24/2.58	13	0.8	9.3	0.7	40×0.10	60×0.20	3.6	83	8121.8	0.153
	3	150	30/2.58	14.6	0.8	9.3	0.7	40×0.10	60×0.20	3.7	86.6	9268.2	0.124
	3	185	37/2.58	16.2	0.8	9.3	0.7	40×0.10	60×0.20	3.8	90.3	10554.7	0.0991
	3	240	48/2.58	18.5	0.8	9.3	0.7	40×0.10	60×0.20	4	95.6	12561.9	0.0754
	3	300	60/2.58	20.6	0.8	9.3	0.7	40×0.10	60×0.20	4.1	100.3	14629.1	0.0601
26/35KV	3	400	61/2.94	23.8	0.8	9.3	0.7	40×0.10	60×0.20	4.4	107.8	17938.4	0.047
	3	50	10/2.58	8.4	0.8	10.5	0.7	40×0.10	60×0.20	3.5	78	5885	0.387
	3	70	19/2.18	10	0.8	10.5	0.7	40×0.10	60×0.20	3.6	81.7	6767.6	0.268
	3	95	19/2.58	11.6	0.8	10.5	0.7	40×0.10	60×0.20	3.7	85.3	7835.1	0.193
	3	120	24/2.58	13	0.8	10.5	0.7	40×0.10	60×0.20	3.8	88.5	8829.7	0.153
	3	150	30/2.58	14.6	0.8	10.5	0.7	40×0.10	60×0.20	3.9	92.2	10006.5	0.124
	3	185	37/2.58	16.2	0.8	10.5	0.7	40×0.10	60×0.20	4	95.8	11319.8	0.0991
	3	240	48/2.58	18.5	0.8	10.5	0.7	40×0.10	60×0.20	4.2	101.2	13371.4	0.0754
	3	300	60/2.58	20.6	0.8	10.5	0.7	40×0.10	60×0.20	4.3	105.9	15475.3	0.0601
3	400	61/2.94	23.8	0.8	10.5	0.7	40×0.10	60×0.20	4.6	113.4	18844.4	0.047	