

Rated Voltage	No. of CORES	CORSS SECTIONAL(MM2)	CONDUCTOR	CORE DIAMETER (MM)	CONDUCTOR SHIELD THICKNESS(MM)	INSULATION THICKNESS(MM)	NON METAL SHIELD SPEC. (MM)	METAL SHIELD SPEC. (MM)	BELT (MM)	JACKET THICKNESS (MM)	OVERALL DIAMETER (MM)	WEIGHT (KG/KM)
3.6/6KV	3	3×25	7/2.18	6	0.8	2.5	0.7	30×0.10	60×0.20	2.1	35.6	1674.8
	3	3×35	7/2.58	7	0.8	2.5	0.7	30×0.10	60×0.20	2.1	37.8	2030.8
	3	3×50	10/2.58	8.4	0.8	2.5	0.7	30×0.10	60×0.20	2.2	41	2549.1
	3	3×70	19/2.18	10	0.8	2.5	0.7	30×0.10	60×0.20	2.4	44.8	3260.6
	3	3×95	19/2.58	11.6	0.8	2.5	0.7	40×0.10	60×0.20	2.5	48.5	4141
	3	3×120	24/2.58	13	0.8	2.5	0.7	40×0.10	60×0.20	2.6	51.7	4968.7
	3	3×150	30/2.58	14.6	0.8	2.5	0.7	40×0.10	60×0.20	2.7	55.3	5955.5
	3	3×185	37/2.58	16.2	0.8	2.5	0.7	40×0.10	60×0.20	2.8	59	7081.9
	3	3×240	48/2.58	18.5	0.8	2.6	0.7	40×0.10	60×0.20	3	64.8	8892.8
	3	3×300	60/2.58	20.6	0.8	2.8	0.7	40×0.10	60×0.20	3.2	70.5	10875.2
6/6KV	3	3×25	7/2.18	6	0.8	3.4	0.7	30×0.10	60×0.20	2.2	39.7	1913.5
	3	3×35	7/2.58	7	0.8	3.4	0.7	30×0.10	60×0.20	2.3	42	2299.2
	3	3×50	10/2.58	8.4	0.8	3.4	0.7	30×0.10	60×0.20	2.4	45.2	2837.2
	3	3×70	19/2.18	10	0.8	3.4	0.7	40×0.10	60×0.20	2.5	48.9	3551.8
	3	3×95	19/2.58	11.6	0.8	3.4	0.7	40×0.10	60×0.20	2.6	52.5	4451.6
	3	3×120	24/2.58	13	0.8	3.4	0.7	40×0.10	60×0.20	2.7	55.8	5298.8
	3	3×150	30/2.58	14.6	0.8	3.4	0.7	40×0.10	60×0.20	2.8	59.4	6306.2
	3	3×185	37/2.58	16.2	0.8	3.4	0.7	40×0.10	60×0.20	2.9	63.1	7453.3
	3	3×240	48/2.58	18.5	0.8	3.4	0.7	40×0.10	60×0.20	3.1	68.4	9253.6
	3	3×300	60/2.58	20.6	0.8	3.4	0.7	40×0.10	60×0.20	3.3	73.3	11175.4
6/10KV	3	3×25	7/2.18	6	0.8	3.4	0.7	30×0.10	60×0.20	2.2	39.7	1913.5
	3	3×35	7/2.58	7	0.8	3.4	0.7	30×0.10	60×0.20	2.3	42	2299.2
	3	3×50	10/2.58	8.4	0.8	3.4	0.7	30×0.10	60×0.20	2.4	45.2	2837.2
	3	3×70	19/2.18	10	0.8	3.4	0.7	40×0.10	60×0.20	2.5	48.9	3551.8
	3	3×95	19/2.58	11.6	0.8	3.4	0.7	40×0.10	60×0.20	2.6	52.5	4451.6
	3	3×120	24/2.58	13	0.8	3.4	0.7	40×0.10	60×0.20	2.7	55.8	5298.8
	3	3×150	30/2.58	14.6	0.8	3.4	0.7	40×0.10	60×0.20	2.8	59.4	6306.2
	3	3×185	37/2.58	16.2	0.8	3.4	0.7	40×0.10	60×0.20	2.9	63.1	7453.3
	3	3×240	48/2.58	18.5	0.8	3.4	0.7	40×0.10	60×0.20	3.1	68.4	9253.6
	3	3×300	60/2.58	20.6	0.8	3.4	0.7	40×0.10	60×0.20	3.3	73.3	11175.4
8.7/10KV	3	3×25	7/2.18	6	0.8	4.5	0.7	30×0.10	60×0.20	2.4	44.8	2251.6
	3	3×35	7/2.58	7	0.8	4.5	0.7	40×0.10	60×0.20	2.5	47.2	2655.9
	3	3×50	10/2.58	8.4	0.8	4.5	0.7	40×0.10	60×0.20	2.6	50.4	3217.3
	3	3×70	19/2.18	10	0.8	4.5	0.7	40×0.10	60×0.20	2.7	54	3957.2
	3	3×95	19/2.58	11.6	0.8	4.5	0.7	40×0.10	60×0.20	2.8	57.7	4884.7
	3	3×120	24/2.58	13	0.8	4.5	0.7	40×0.10	60×0.20	2.9	60.9	5754.2
	3	3×150	30/2.58	14.6	0.8	4.5	0.7	40×0.10	60×0.20	3	64.5	6788
	3	3×185	37/2.58	16.2	0.8	4.5	0.7	40×0.10	60×0.20	3.1	68.2	7961.6
	3	3×240	48/2.58	18.5	0.8	4.5	0.7	40×0.10	60×0.20	3.3	73.5	9801.3
	3	3×300	60/2.58	20.6	0.8	4.5	0.7	40×0.10	60×0.20	3.4	78.3	11725.3
3	3×400	61/2.94	23.8	0.8	4.5	0.7	40×0.10	60×0.20	3.7	85.8	14799.2	

Rated Voltage	No. of CORES	CORSS SECTIONAL(MM2)	CONDUCTOR	CORE DIAMETER (MM)	CONDUCTOR SHIELD THICKNESS(MM)	INSULATION THICKNESS(MM)	NON METAL SHIELD SPEC. (MM)	METAL SHIELD SPEC. (MM)	BELT (MM)	JACKET THICKNESS (MM)	OVERALL DIAMETER (MM)	WEIGHT (KG/KM)
8.7/15KV	3	3×25	7/2.18	6	0.8	4.5	0.7	30×0.10	60×0.20	2.4	44.8	2251.6
	3	3×35	7/2.58	7	0.8	4.5	0.7	40×0.10	60×0.20	2.5	47.2	2655.9
	3	3×50	10/2.58	8.4	0.8	4.5	0.7	40×0.10	60×0.20	2.6	50.4	3217.3
	3	3×70	19/2.18	10	0.8	4.5	0.7	40×0.10	60×0.20	2.7	54	3957.2
	3	3×95	19/2.58	11.6	0.8	4.5	0.7	40×0.10	60×0.20	2.8	57.7	4884.7
	3	3×120	24/2.58	13	0.8	4.5	0.7	40×0.10	60×0.20	2.9	60.9	5754.2
	3	3×150	30/2.58	14.6	0.8	4.5	0.7	40×0.10	60×0.20	3	64.5	6788
	3	3×185	37/2.58	16.2	0.8	4.5	0.7	40×0.10	60×0.20	3.1	68.2	7961.6
	3	3×240	48/2.58	18.5	0.8	4.5	0.7	40×0.10	60×0.20	3.3	73.5	9801.3
	3	3×300	60/2.58	20.6	0.8	4.5	0.7	40×0.10	60×0.20	3.4	78.3	11725.3
12/20KV	3	3×35	7/2.58	7	0.8	5.5	0.7	40×0.10	60×0.20	2.6	51.7	2992.9
	3	3×50	10/2.58	8.4	0.8	5.5	0.7	40×0.10	60×0.20	2.7	54.9	3574.5
	3	3×70	19/2.18	10	0.8	5.5	0.7	40×0.10	60×0.20	2.8	58.5	4337.1
	3	3×95	19/2.58	11.6	0.8	5.5	0.7	40×0.10	60×0.20	2.9	62.2	5287.4
	3	3×120	24/2.58	13	0.8	5.5	0.7	40×0.10	60×0.20	3	65.4	6177
	3	3×150	30/2.58	14.6	0.8	5.5	0.7	40×0.10	60×0.20	3.1	69.1	7235
	3	3×185	37/2.58	16.2	0.8	5.5	0.7	40×0.10	60×0.20	3.3	72.9	8463
	3	3×240	48/2.58	18.5	0.8	5.5	0.7	40×0.10	60×0.20	3.4	78.1	10304.9
	3	3×300	60/2.58	20.6	0.8	5.5	0.7	40×0.10	60×0.20	3.6	83	12294.3
	3	3×400	61/2.94	23.8	0.8	5.5	0.7	40×0.10	60×0.20	3.8	90.3	15377.9
18/30KV	3	3×50	10/2.58	8.4	0.8	8	0.7	40×0.10	60×0.20	3.1	66.5	4635.5
	3	3×70	19/2.18	10	0.8	8	0.7	40×0.10	60×0.20	3.2	70.1	5457.3
	3	3×95	19/2.58	11.6	0.8	8	0.7	40×0.10	60×0.20	3.3	73.8	6467.1
	3	3×120	24/2.58	13	0.8	8	0.7	40×0.10	60×0.20	3.4	77	7409.2
	3	3×150	30/2.58	14.6	0.8	8	0.7	40×0.10	60×0.20	3.5	80.6	8525
	3	3×185	37/2.58	16.2	0.8	8	0.7	40×0.10	60×0.20	3.6	84.3	9780.7
	3	3×240	48/2.58	18.5	0.8	8	0.7	40×0.10	60×0.20	3.8	89.6	11742.3
	3	3×300	60/2.58	20.6	0.8	8	0.7	40×0.10	60×0.20	3.9	94.3	13770.1
21/35KV	3	3×50	10/2.58	8.4	0.8	9.3	0.7	40×0.10	60×0.20	3.3	72.5	5259.5
	3	3×70	19/2.18	10	0.8	9.3	0.7	40×0.10	60×0.20	3.4	76.1	6112
	3	3×95	19/2.58	11.6	0.8	9.3	0.7	40×0.10	60×0.20	3.5	79.8	7152.4
	3	3×120	24/2.58	13	0.8	9.3	0.7	40×0.10	60×0.20	3.6	83	8121.8
	3	3×150	30/2.58	14.6	0.8	9.3	0.7	40×0.10	60×0.20	3.7	86.6	9268.2
	3	3×185	37/2.58	16.2	0.8	9.3	0.7	40×0.10	60×0.20	3.8	90.3	10554.7
	3	3×240	48/2.58	18.5	0.8	9.3	0.7	40×0.10	60×0.20	4	95.6	12561.9
	3	3×300	60/2.58	20.6	0.8	9.3	0.7	40×0.10	60×0.20	4.1	100.3	14629.1
26/35KV	3	3×400	61/2.94	23.8	0.8	9.3	0.7	40×0.10	60×0.20	4.4	107.8	17938.4
	3	3×50	10/2.58	8.4	0.8	10.5	0.7	40×0.10	60×0.20	3.5	78	5885
	3	3×70	19/2.18	10	0.8	10.5	0.7	40×0.10	60×0.20	3.6	81.7	6767.6
	3	3×95	19/2.58	11.6	0.8	10.5	0.7	40×0.10	60×0.20	3.7	85.3	7835.1
	3	3×120	24/2.58	13	0.8	10.5	0.7	40×0.10	60×0.20	3.8	88.5	8829.7
	3	3×150	30/2.58	14.6	0.8	10.5	0.7	40×0.10	60×0.20	3.9	92.2	10006.5
	3	3×185	37/2.58	16.2	0.8	10.5	0.7	40×0.10	60×0.20	4	95.8	11319.8
	3	3×240	48/2.58	18.5	0.8	10.5	0.7	40×0.10	60×0.20	4.2	101.2	13371.4
	3	3×300	60/2.58	20.6	0.8	10.5	0.7	40×0.10	60×0.20	4.3	105.9	15475.3
3	3×400	61/2.94	23.8	0.8	10.5	0.7	40×0.10	60×0.20	4.6	113.4	18844.4	