

SOLAR CABLE TYPE:

TYPE	CrossSection	Conductor Structure	ConductorDiameter	OuterDiameter	Conductor	Rated Voltage	Rated Current
	mm ²	No.OD (mm)	mm	mm	Ω/Km	V AC/DC	A
1	2.5	49/0.25	2	5.2	8.21	1000/1800	30
1	4	56/0.30	2.6	6.2	5.09	1000/1800	50
1	6	84/0.30	3.3	7.2	3.39	1000/1800	70
1	10	74/0.40	4.4	8.3	2.12	1000/1800	95
2	2.5	49/0.25	2	6.2*9.90	8.06	1000/1800	30
2	4	56/0.30	2.6	6.9*11.30	4.97	1000/1800	50
2	6	84/0.30	3.3	7.1*14.50	3.52	1000/1800	70

PARAMETER:

TYPE	CrossSection	Conductor Structure	ConductorDiameter	OuterDiameter	Conductor	Rated Voltage	Rated Current
	mm ²	No.OD (mm)	mm	mm	Ω/Km	V AC/DC	A
1	2.5	49/0.25	2	5.2	8.21	1000/1800	30
1	4	56/0.30	2.6	6.2	5.09	1000/1800	50
1	6	84/0.30	3.3	7.2	3.39	1000/1800	70
1	10	74/0.40	4.4	8.3	2.12	1000/1800	95
2	2.5	49/0.25	2	6.2*9.90	8.06	1000/1800	30
2	4	56/0.30	2.6	6.9*11.30	4.97	1000/1800	50
2	6	84/0.30	3.3	7.1*14.50	3.52	1000/1800	70