

Code Name	Phase Conductor			Bare Neutral		Approx.Weight	
	Size	Stranding	Insulation Thickness	Size	Stranding	XLPE	PE
	AWG	-	mil	AWG	-	lbs/1000ft	
AAC Neutral Messenger							
Pekingese	6	Solid	45	6	7/w	63.5	61.7
Collie	6	7/w	45	6	7/w	66.8	63.1
Dachshund	4	Solid	45	4	7/w	95.5	93.4
Spaniel	4	7/w	45	4	7/w	100.5	95.4
Doberman	2	7/w	45	2	7/w	152.7	145.7
Malemute	1/0	19/w	60	1/0	7/w	242.6	234.2
6201 Alloy Neutral Messenger							
Chihuahua	6	Solid	45	6	7/w	67.6	65.8
Vizsla	6	7/w	45	6	7/w	70.9	67.2
Harrier	4	Solid	45	4	7/w	102	99.9
Code Name	Phase Conductor			Bare Neutral		Approx.Weight	
	Size	Stranding	Insulation Thickness	Size	Stranding	XLPE	PE
	AWG	-	mil	AWG	-	lbs/1000ft	
ACSR Neutral Messenger							
Setter	6	Solid	45	6	6/1	75	73.2
Shepherd	6	7/w	45	6	6/1	78.3	74.6
Eskimo	4	Solid	45	4	6/1	113.7	111.6
Terrier	4	7/w	45	4	6/1	118.7	113.6
Chow	2	7/w	45	2	6/1	181.7	174.7
Bull	1/0	19/w	60	1/0	6/1	288.7	280.3
6201 Alloy Neutral Messenger							
Whippet	4	7/w	45	4	7/w	107	101.9
Schnauzer	2	7/w	45	2	7/w	163.3	156.2
Heeler	1/0	19/w	60	1/0	7/w	259.2	250.8